

### Overview

Infrared (IR) Carbon Dioxide Gas Sensor Module is network-enabled to provide the interface needed to your plant-wide control system, whether it be 4-20 mA, Modbus, HART, relay contacts or SentryBus. This USA-made, stand-alone smart gas sensor module is loaded with features you need. As usual, Sierra Monitor A gas detector with a Sierra Monitor pedigree, Factory Mutual approved and ready to Manage Your Gas Risk. The 5100-88-IT provides all the built-in features desired by instrumentation and safety professionals, including:

- Modbus RTU RS-485 interface
- 4-20 mA output
- HART Interface
- SMC Sentry digital bus interface
- Optional Integral alarm relays - Alarm, Warning & Trouble
- Aluminum or 316 Stainless Steel enclosure
- Annual calibration frequency
- Interface to multiple protocols
- Integral scrolling LED display



The 5100-88-IT can be used as a 4-20 mA component or as a Modbus RTU node. For higher level system capability the module can interface directly to Sierra Monitor's Sentry Controller. As part of a Sentry system the user gains capability of system Modbus serial communications, extensive diagnostic features, area and zone alarm management, WebServer interface and multiplexing sensor connections.

### How It Works

Carbon Dioxide absorbs infrared light energy at defined wavelengths, providing an absorption signature for CO<sub>2</sub>. The principle of an infrared detector is based upon the absorption of the infrared light at a specific wavelength as it passes through the gas. The more of the absorbing gas that is present, the more light is absorbed. The detector measures the energy from an infrared light beam at a wavelength that is absorbed by the gas and compares it to the energy emitted by the source. The difference in energy received by the detector indicates the level of gas in the atmosphere.

#### Features

- Non-intrusive calibration
- Network-compatible with Modbus, 4-20 mA, Sentry bus, HART and relay interface
- Local scrolling display

#### Benefits

- Able to easily and quickly calibrate module without declassifying the area
- Easy to install in a variety of field applications plus easy to obtain critical safety information wherever needed
- Ease of calibration and easy access to gas concentration, relay status and diagnostics

**Sensor**

**Type:** Infrared, Dual Wavelength

**Performance**

**Range:** 0-5000 PPM Carbon Dioxide

**Repeatability:** +/-1%

**Accuracy:** +/- 2%

**Sensor Life:** Typically >5 years

**Heated Sensor:** Heated cell to prevent condensation

**Response Time:** T60<20sec

**Options**

**Relays:** 5 amp Alarm, Warning (0.25 amp Trouble)

5A@ 250 VAC, 5A@ 30VDC (Alarm, Warning)

Board includes auxiliary connection for Sentry multiplexing

**HART:** Termination board includes HART, Modbus RS-485, 4-20mA, Digital Input, 2A Relay output, No Sentry Bus

**Power**

**Power consumption:** 3 watts

**Input voltage:** 24 VDC nominal: 10-30VDC

**Output**

**Display:** Fixed and Scrolling LED

**Signal Output:** Sentry digital bus

Analog 4-20 mA

3-wire Non-Isolated

4-wire Isolated

Serial RS-485 Modbus RTU

**Relay:** Optional

**Operating Range**

**Ambient Temp Range:** -4<sup>o</sup> to 140<sup>o</sup>F (-20<sup>o</sup> to 60<sup>o</sup>C)

**Relative Humidity:** 0-99% Non-Condensing

**Construction**

**Dimensions:** (HxWxD)

(A1) 7.8 x 5.7 x 3.9 in

(19.8 x 14.5 x 9.9 cm)

(A2) 8.1 x 4.8 x 4.9 in.

(21 x 12 x 12 cm)

(S1 & S2) 7.5 x 4.4 x 4.9 in.

(19 x 11 x 12 cm)

**Weight:** (A1) = 3.4 lb. (1.5 Kg)

(A2) = 5.4 lb. (2.5 Kg)

(S1 & S2) = 7.2 lb. (3.3 Kg)

**Housing:** Epoxy coated Aluminum or 316 Stainless Steel

**Hazardous Area Classification**

Explosion proof, Class I, Div. 1, Groups B, C, D

Class I, Zone 1, Group IIC, IP66, IP65, NEMA 4X, T6

TA = -40<sup>o</sup>C to 85<sup>o</sup>C II2 GD, Ex d IIC

**Warranty:** 2 years



\*Specifications subject to change without notice

**Ordering Information:** The following part number is essential in selection of the correct product. Please build up the desired part by inserting the code for each element into the appropriate space (ie. 5100-88-IT-S1-02-00-2-0).

Model	Enclosure	Relay/Connection Output	XX	Sensor Protection	Remote Option
5100-88-IT	↓ - A1 = AL ¾" NPT - A2 = AL M20 x 1.5 - S1 = SS ¾" NPT - S2 = SS M20 x 1.5	↓ - 01 = No Relays (Std) - 02 = Relays Option - 05 = HART Option	↓ - 00 = Std (0-5000PPM) - 81 = 0-5% Vol. - 82 = 0-20% Vol.	↓ - 0 = Standard - 2 = Conformal Sensor	↓ - 0 = None

**Accessories:**

5311-00 Rainshield  
5311-02 Rainshield with calibration port

**Calibration Accessories:**

5358-01 Calibration Head, Standard  
5360-00 Calibration Gas Delivery Fitting

**Calibrators High Capacity:**

1250-01 Gas Sensor Calibration Kit, Type A  
1260-80 2000 PPM CO<sub>2</sub> Gas Cylinder Type A